

Prada Grey

Size: 600X600 mm | **Design:** Stone | **Finish:** Matte Finish in Ceramic Floor Body | **Series:** DuraDigi



Front View



Scale View

Packaging Details

| Size | No. of tiles in box | Coverege Area | |
|------------|---------------------|---------------|-------|
| | | sq/mtr | sq/ft |
| 600X600 mm | 4.0 | 1.44 | 15.5 |

Technical Specification

| Sr.No. | Test Description | Standard Test Method | ISO13006:2018 Specification B1a | Nitco's Value |
|---|-----------------------|--|---------------------------------|---------------|
| | | 1 | | |
| Length and Width | ISO 10545-2 / EN 98 | $\pm 0.3 \% (\text{Max } \pm 1.0 \text{ mm}) \pm 0.15\%$ | | 2 |
| Thickness | ISO 10545-2 / EN 98 | $\pm 5.0 \% (\text{Max } \pm 0.5\text{mm}) \pm 5.0\%$ | | 3 |
| Straightness of sides (%) | ISO 10545-2 / EN 98 | $\pm 0.3 \% (\text{Max } \pm 0.8 \text{ mm}) \pm 0.13\%$ | | 4 |
| Rectangularity | ISO 10545-2 / EN 98 | $\pm 0.3 \% (\text{Max } \pm 1.5 \text{ mm}) \pm 0.15\%$ | | 5 |
| Surface Flatness | ISO 10545-2 / EN 98 | $\pm 0.4 \% (\text{max } +1.8 \text{ mm}) \pm 0.30\%$ | | 6 |
| Surface Quality | ISO 10545-2 / EN 98 | 95% free from visible defects | >95% free from visible defects | 7 |
| Water Absorption | ISO 10545-3 / EN 99 | 3% < E 6% | 3-6% | 8 |
| Breaking Strength, N | ISO 10545-4 / EN 100 | Min 1000 N | >1100 N | 9 |
| Modulus of Rupture (MOR), N/mm ² | ISO 10545-4 / EN 100 | Min. 22 | >22 | 10 |
| Abrasion Resistance (PEI III, IV, V) | ISO 10545-7 / EN 154 | As Specified by Manufacture | As Specified | 11 |
| Thermal Shock Resistance | ISO 10545-9 / EN 104 | Resistant to 10 cycle | Resistant | 12 |
| Crazing Resistance | ISO 10545-11 / EN 105 | No Crazing | Resistant | 13 |

WANT TO GET IN TOUCH WITH US?

Toll Free: 1800 266 4826 | Email: marketing@nitco.in