


# NITCO

## Orbit Tan

**Size:** 300 X 300 mm | **Design:** Modern | **Finish:** Matte Finish in Vitrified Heavy Duty Body | **Series:** Kratos



Front View



Scale View

### Packaging Details

| Size         | No. of tiles in box | Coverege Area |       | Thickness |
|--------------|---------------------|---------------|-------|-----------|
|              |                     | sq/mtr        | sq/ft |           |
| 300 X 300 mm | 8.00                | 0.72          | 7.75  | 9.50      |

### Technical Specification

| Sr.No. | Test Description              | Standard Test Method | ISO 13006:1998 E Specification | Nitco's Value          |
|--------|-------------------------------|----------------------|--------------------------------|------------------------|
| 1      | Deviation in Length and Width | ISO 10545 - 2        | ± 0.6 % (Max ± 2.0 mm)         | ± 0.2 %                |
| 2      | Deviation in Thickness        | ISO 10545 - 2        | ± 5.0 % ( Max ± 0.5 mm )       | ± 5 %                  |
| 3      | Straightness of Sides         | ISO 10545 - 2        | ± 0.5 % ( Max ± 1.5 mm )       | ± 0.2 %                |
| 4      | Rectangularity                | ISO 10545 - 2        | ± 0.5 % ( Max ± 2.0 mm )       | ± 0.3 %                |
| 5      | Water Absorption              | ISO 10545 - 3        | ± 0.5 % ( Max ± 2.0 mm )       | ± 0.20%                |
| 6      | Mohs Hardness                 | En- 101              | >6                             | >7                     |
| 7      | Flextural Strength            | ISO 10545 - 4        | >35 N/mm <sup>3</sup>          | >=35 N/mm <sup>3</sup> |
| 8      | Deep Abrasion Resistance      | ISO 10545 - 6        | < 175 Cu.mm                    | < 175 Cu.mm            |
| 9      | Breaking Strength             | ISO 10545 - 4        | >1000 N                        | >1200 N                |
| 10     | Chemical Resistance           | ISO 10545 - 13       | No Damage                      | No Damage              |
| 11     | Thermal Shock Resistance      | ISO 10545 - 9        | No Damage                      | No Damage              |
| 12     | Color Resistance              | DIN 51094            | No Damage                      | No Damage              |
| 13     | Stains Resistance             | ISO 10545 - 14       | Resistant                      | Resistant              |
| 14     | Moisture Expansion            | ISO 10545 - 10       | NIL                            | NIL                    |

WANT TO GET IN TOUCH WITH US?

Toll Free: 1800 266 4826 | Email: marketing@nitco.in